

ÖZTİRYAKİLER

Cumhuriyet Mah. Hadımköy Yolu Cad. No:8 Büyükçekmece-İstanbul-TURKEY

e-mail: export@oztiryakiler.com.tr web: www.oztiryakiler.com.tr

COLD UNITS Code: 7919.06NLS.10 GN 2/1 Size Double Section Refrigerator / Freezer Model: GN 600.10 NLS



MAIN FEATURES

- * GN 2/1 Size Refrigerator / Freezer With Double Door
- * 304 quality stainless steel
- * Operating temperature Top Cover -2/+8°C, Bottom Cover -18/-20°C
- * Static Cooling System.
- * Clean-free condenser
- * The inner liners and inner lower base which are deep drawn comply with the highest hygiene standards with rounded corners and are made of stainless steel.
- * Mono-block design
- * Internal led light
- * Wide magnetic removable gasket with triple indulation area provides an effective seal which reduces heat lost.
- * 40-42 Kg/m3 density environment friendly HFC-Free Polyurethane insulation for low energy consumption (80 mm)
- * Full frontal water-proof design (IP21)
- * Reversible door allows the appliances to be adapted to any individual installation site.

OPTIONS

* Wheels, Stainless steel shelf

ACCESSORIES

*GN 2/1 PVC shelf x2

STANDARTS

*EN 60335-1 European Standard relating to safety of household and similar electrical appliances

*EN 60335-2-89 Particular requirements for commercial refrigerating appliances with an incorporated or remote refrigerant condensing unit or compressor






ÖZTİRYAKİLER


Cumhuriyet Mah. Hadımköy Yolu Cad. No:8 Büyükçekmece-İstanbul-TURKEY


e-mail: export@oztiryakiler.com.tr web: www.oztiryakiler.com.tr

Code: COLD UNITS
7919.06NLS.10 GN 2/1 Size Double Section Refrigerator / Freezer

Model: GN 600.10 NLS









DIMENSIONS (Net)			DIMENSIONS (Shipping)		
* Depth (mm)	690		* Depth (mm)	890	
* Width (mm)	840		* Width (mm)	740	
* Height (mm)	2100		* Height (mm)	2250	
			* Volume (m3)	1,48	
			* Weight (kg)	126	

TECHNICAL FEATURES

- * Gross Volume: 700 L
- * Temperature range: (Top Cover -2/+8°C) , (Bottom Cover -18/-20°C)
- * Climate Class: CC4
- * Refrigerant: (R134a 80g), (R404a 140g)
- * Refrigeration Capacity: 0,50 kW



ELECTRICITY

- * Power: 0,75 kW
- * Supply Voltage: 220-240 V
- * Frequency: 50-60 Hz



WATER-IN



DRAIN